

TRELLEBORG

T - 8 0 0



TOTAL SOLUTIONS


TRELLEBORG
WHEEL SYSTEMS



PNEUMATIC TIRES



The Trelleborg pneumatic tire range has been developed for heavy duty use on forklift trucks and other industrial vehicles. This line of tires offer customers an additional range of tires besides solid rubber and polyurethane products. All the tires have a lug type tread pattern which provides optimal grip and traction in every condition. The cross-ply or diagonal structure further insures high stability and maximum safety. The casing is of high tensile strength nylon cord which offers good resistance to fatigue and improves comfort.

- **NATURAL RUBBER**
- **GOOD RESISTANCE TO FATIGUE**
- **HIGH STABILITY MAXIMUM SAFETY**
- **OPTIMAL GRIP AND TRACTION**



TRELLEBORG T-800

- **TRELLEBORG ENGINEERED**
- **PREMIUM COMPOUNDS**
- **HIGH RELIABILITY**
- **FOR USE IN INDUSTRIAL APPLICATIONS**
- **AVAILABLE IN POPULAR SIZES**
- **COST EFFECTIVE**



Size	P.R.	Recommended rim	Profile T-800	Inflated dimensions (mm)		Inflation pressure (±15%)		Weight Tire (kg)	Load capacity forklift up to 25 km/h (kg)	
				Width	O.D.	PSI	Bar		Front	Rear
5.00-8	10	3.00	*	132	470	145	10.00	6.2	1415	1090
18x7-8	16	4.33	*	159	456	145	10.00	9.5	2145	1650
6.00-9	12	4.00	*	154	546	145	10.00	9.7	1885	1450
21x8-9	14	6.00	*	195	533	130	9.00	14.0	2535	1950
6.50-10	10	5.00	*	183	598	112	7.75	11.1	1950	1500
23x9-10	20	6.50	*	226	583	145	10.00	22.1	3445	2650
7.00-12	14	5.00	*	190	682	130	9.00	16.0	2755	2120
27x10-12	14	8.00	*	244	690	102	7.00	28.9	3545	2725
7.00-15	14	5.50	*	185	752	127	8.75	21.2	3275	2520
7.50-15	14	6.00	*	215	804	134	9.25	24.5	3640	2800
28x9-15 (8.15-15)	14	7.00	*	218	708	145	10.00	23.7	3900	3000
8.25-15	14	6.50	*	237	836	116	8.00	30.5	4225	3250
250-15	20	7.50	*	236	762	145	10.00	36.7	5040	3875
300-15	20	8.00	*	288	843	130	9.00	44.7	6500	5000

1) The above load capacities are based on available E.T.R.T.O and T.R.A. specifications for load and steering wheels on counterbalanced forklift trucks.

2) The Trelleborg pneumatic tires are available as complete sets (tire/tube/flap) or as tire & flap only.